



PLUS25II Thermal Transfer printer, 200dpi, Eth.

PLUS25II

The PLUS 25II thermal transfer printer was designed to work in different environments, including Retail, small/medium offices, archiving of documents, Healthcare, parcel labeling, Manufacturing and Logistics.

COD: PLUS25II

PLURISERVICE CODE STTTTS081



Retail



Trasporti e
logistica

DESCRIPTION

THERMAL TRANSFER PRINTER, SUITABLE FOR DIFFERENT ENVIRONMENTS.

Its space-saving design and easy ribbon loading make the PLUS25II use practical and fast. Equipped with USB 2.0, Serial, parallel and Ethernet interfaces. 4MB flash standard memory, with 4GB (SD card) option. Its print speed is 6"/sec (152mm/sec) and loads label rolls with external diameter up to 5" (127mm). Adjustable sensor.

TECHNICAL SPECIFICATIONS

Printer language: TSPL-EZ Emulation (compatible with EPL, ZPL, ZPLII)

Dimensions:

7.99"x7.53"x10.2"(203X191,5X259,3mm)

Weight: 4.85 lbs (2.2 kg)

Print speed 6"/sec (152 mm/sec)

MEMORY: 4MB FLASH/8MB SDRAM

INTERFACES: USB, RS232, Parallel, Ethernet, ext. Bluetooth (dongle) option

Black mark adjustable sensor

Ribbon end sensor

Application fields: Retail, Small/medium offices, Healthcare, Archiving of documents.